

ENGINE / DRIVE TRAIN

MODELS Canoe 50

Displacement: 49.6cc / Air cooled / 4 Stroke Single Cylinder

Max Torque: 2.3 lb/ft - 7500 RPM

Max Hp: 3.6 Compression Ratio: 10.5:01

Cooling System: Air Cooled Transmission: C.V.T.

Clutch: Centrifugal Type

Drive: Belt

Starter: Electrical Starter / Kick Engine Oil: 10W/40 or 15W/40

Carburetor Brand: Deni PD18J B

Ignition: CDI Spark Plug: NGK

Battery: YTX7A-BS / 12V/7A

Top Speed: 30 mph

CHASSIS / SUSPENSION / BRAKES

Frame: High Strength Steel
Front Suspension: Telescopic Fork
Rear Suspension: Dual Swing

Front Brakes: Disc

Rear Brakes: Drum
Front Tires: 3.50-10
Rear Tires: 3.50-10
Wheel: Aluminum

CAPACIITIES / DIMENSIONS

Weight Capacity: 330.69 Lbs
Net Weight: 182.98 Lbs

Fuel: Unleaded (90 octane or higher)

Fuel Capacity: 1.10 gallons

Dimension: L 70.07" x W 25.19" x H 42.51"

Seat Height: 29.7" Wheelbase: 48.03" Age Recommendation: 14+

ADDITIONAL INFO

Government Certifications: EPA & DOT Approved, C.A.R.B. Approved for CA

Charging Port: Built-in USB Charging Port

Warranty: 12 Months Limited Parts Warranty

MPG: Up to 110+ MPG